



## TECHNICAL DATA SHEET

CMC TYPE	CMC 64160
<b>Product description</b>	CMC 64160 is a paper tape with rubber adhesive for winding insulation or winding protection.
<b>Backing material</b>	impregnated crepe paper
Colour	chamois
Total thickness in mm	ca. 0.185
<b>Adhesive properties</b>	
Type of adhesive	rubber
Adhesive strength in N/cm according to internal method PV 1006-32 (180° peel from steel)	≥ 2.5
<b>Thermal properties</b>	
Temperature performance (max.) in °C	105
Short term temperature performance	130°C for 2 h or 150°C for 1 h
Insulation class according to IEC 60085	A
<b>Electrical properties</b>	
Breakdown voltage based on IEC 60243-1 in $V_{eff}$ .	≥ 1'000
<b>Mechanical properties</b>	
Tensile strength in N/cm	≥ 30
Elongation at break in %	≥ 10
<b>Other properties</b>	 

Storage conditions: cool and dry (15 - 25°C, < 65% rel. humidity)

11/19

Quality guarantee: 6 months

The technical data are average values and subject to change without notice. They are not intended to replace user's testing.

Note on REACH: Some of our products do contain substances from the so-called candidate list. Please visit <https://en.cmc.de/page/reach> and check whether or not a purchased product is listed in our REACH statement and therefore does contain one or more SVHCs.